

Facility/Project Name gINT Example	Local Grid Location of Well 300 ft. <input checked="" type="checkbox"/> N. <input type="checkbox"/> S. 100 ft. <input checked="" type="checkbox"/> E. <input type="checkbox"/> W.		Well Name MW-1	
Facility License, Permit or Monitoring No. 123456789	Local Grid Origin <input checked="" type="checkbox"/> (estimated: <input type="checkbox"/>) or Well Location <input type="checkbox"/> Lat. 44° 40' 30.0" Long. 90° 20' 20.0" or		Wis. Unique Well No. AA000	DNR Well Number 123
Facility ID 4321	St. Plane 123,456 ft. N., 654,321 ft. E. S/ <input checked="" type="checkbox"/> N		Date Well Installed 07/08/1999	
Type of Well Well Code 62/as	Section Location of Waste/Source NE 1/4 of SE 1/4 of Sec. 8, T. 5 N, R. 11 <input checked="" type="checkbox"/> E <input type="checkbox"/> W		Well Installed By: (Person's Name and Firm) John Smith	
Distance from Waste/Source 100 ft.	Enf. Stds. Apply <input checked="" type="checkbox"/>	Location of Well Relative to Waste/Source u <input checked="" type="checkbox"/> Upgradient s <input type="checkbox"/> Sidegradient d <input type="checkbox"/> Downgradient n <input type="checkbox"/> Not Known	Gov. Lot Number 543	ABC Well Installers

A. Protective pipe, top elevation	107.25 ft. MSL	1. Cap and lock?	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
B. Well casing, top elevation	106.55 ft. MSL	2. Protective cover pipe:	
C. Land surface elevation	105.2 ft. MSL	a. Inside diameter:	3.5 in.
D. Surface seal, bottom	104.2 ft. MSL or 1.0 ft.	b. Length:	5.0 ft.
		c. Material:	Steel <input checked="" type="checkbox"/> 0.4 Other <input type="checkbox"/>
		d. Additional protection?	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
		If yes, describe:	
		3. Surface seal:	Bentonite <input checked="" type="checkbox"/> 3.0 Concrete <input type="checkbox"/> 0.1 Other <input type="checkbox"/>
		4. Material between well casing and protective pipe:	Bentonite <input checked="" type="checkbox"/> 3.0 Other <input type="checkbox"/>
		5. Annular space seal:	a. Granular/Chipped Bentonite <input checked="" type="checkbox"/> 3.3 b. ___ Lbs/gal mud weight . . . Bentonite-sand slurry <input type="checkbox"/> 3.5 c. ___ Lbs/gal mud weight . . . Bentonite slurry <input type="checkbox"/> 3.1 d. ___ % Bentonite . . . Bentonite-cement grout <input type="checkbox"/> 5.0 e. 3 Ft ³ volume added for any of the above f. How installed: Tremie <input type="checkbox"/> 0.1 Tremie pumped <input type="checkbox"/> 0.2 Gravity <input checked="" type="checkbox"/> 0.8
12. USCS classification of soil near screen:		6. Bentonite seal:	a. Bentonite granules <input type="checkbox"/> 3.3 b. <input type="checkbox"/> 1/4 in. <input checked="" type="checkbox"/> 3/8 in. <input type="checkbox"/> 1/2 in. Bentonite chips <input checked="" type="checkbox"/> 3.2 c. ___ Other <input type="checkbox"/>
GP <input type="checkbox"/> GM <input type="checkbox"/> GC <input type="checkbox"/> GW <input type="checkbox"/> SW <input type="checkbox"/> SP <input type="checkbox"/> SM <input type="checkbox"/> SC <input type="checkbox"/> ML <input type="checkbox"/> MH <input type="checkbox"/> CL <input checked="" type="checkbox"/> CH <input type="checkbox"/> Bedrock <input type="checkbox"/>		7. Fine sand material: Manufacturer, product name & mesh size	a. ACME Monterey Sand #20 <input checked="" type="checkbox"/> b. Volume added 0.5 ft ³
13. Sieve analysis attached? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		8. Filter pack material: Manufacturer, product name & mesh size	a. ACME 1/8" Pea Gravel <input checked="" type="checkbox"/> b. Volume added 0.5 ft ³
14. Drilling method used: Rotary <input checked="" type="checkbox"/> 5.0 Hollow Stem Auger <input type="checkbox"/> 4.1 Other <input type="checkbox"/>		9. Well casing:	Flush threaded PVC schedule 40 <input checked="" type="checkbox"/> 2.3 Flush threaded PVC schedule 80 <input type="checkbox"/> 2.4 Other <input type="checkbox"/>
15. Drilling fluid used: Water <input type="checkbox"/> 0.2 Air <input type="checkbox"/> 0.1 Drilling Mud <input checked="" type="checkbox"/> 0.3 None <input type="checkbox"/> 9.9		10. Screen material: Schedule 40 PVC <input checked="" type="checkbox"/>	a. Screen Type: Factory cut <input checked="" type="checkbox"/> 1.1 Continuous slot <input type="checkbox"/> 0.1 Other <input type="checkbox"/>
16. Drilling additives used? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		b. Manufacturer ACME	c. Slot size: 0.010 in. d. Slotted length: 4.0 ft.
Describe _____		11. Backfill material (below filter pack):	None <input type="checkbox"/> 1.4 Cuttings <input checked="" type="checkbox"/>
17. Source of water (attach analysis, if required): Street hydrant 100 feet west of hole			
E. Bentonite seal, top	97.2 ft. MSL or 8.0 ft.		
F. Fine sand, top	96.2 ft. MSL or 9.0 ft.		
G. Filter pack, top	95.7 ft. MSL or 9.5 ft.		
H. Screen joint, top	95.6 ft. MSL or 9.6 ft.		
I. Well bottom	91.7 ft. MSL or 13.5 ft.		
J. Filter pack, bottom	91.2 ft. MSL or 14.0 ft.		
K. Borehole, bottom	88.2 ft. MSL or 17.0 ft.		
L. Borehole, diameter	6.0 in.		
M. O.D. well casing	3.50 in.		
N. I.D. well casing	3.00 in.		

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature	Firm	Tel:
	ACME CONSULTING	534 123 4567
	1234 Anystreet Somewhere, Someplace	Fax: 534 321 4567

Please complete both Forms 4400-113A and 4400-113B and return them to the appropriate DNR office and bureau. Completion of these reports is required by chs. 160, 281, 283, 289, 291, 292, 293, 295, and 299, Wis. Stats., and ch. NR 141, Wis. Adm. Code. In accordance with chs. 281, 289, 291, 292, 293, 295, and 299, Wis. Stats., failure to file these forms may result in a forfeiture of between \$10 and \$25,000, or imprisonment for up to one year, depending on the program and conduct involved. Personally identifiable information on these forms is not intended to be used for any other purpose. NOTE: See the instructions for more information, including where the completed forms should be sent.