

**Project:** gINT Example

**Boring:** MW-1

Pg. 1 of 1

Drilling Co: AAAAA Drilling

Drilling Method: 8" Hollow stem flight augers

Date Started: 12/16/02

Location: 30 feet north west of corner of

Sampler / Drop: 2" OD Split Spoon/30"

Date Completed: 12/17/02

State & Main streets.

Logged by: I. Core

Reviewed by: A. Bore

Surface Elev.: 123.4 MSL

Water Depths: ∇ ATD 24

∇ At Completion 20

DEPTH - FT.	FIELD BOX WITH LOCKING CAP	N VALUE	% RECOVERY	PID	SAMPLES	GRAPHIC LOG	DESCRIPTION	DEPTH - FT.	USCS SYMBOL	ESTIMATED % OF			MOISTURE
										GR	SA	FI	
0							Well graded brownish-red GRAVEL WITH SAND. Cobbles present. Gravel is subrounded to rounded.						
5	CEMENT GROUT							5	GW	65	30	5	D
6	BENTONITE PELLETS	60	100	999			grades sandier						
7	2 INCH SCH. 40 PVC BLANK CASING												
8	2 INCH SCH. 40 PVC 0.020" SLOT SIZE SCREENED CASING						Well graded brownish-red GRAVELLY SAND. Occasional cobbles.	10	SW	35	60	5	M
9	FILTER PACK, CSSI 8-12	40	90	9999									
14		34	80				Poorly graded reddish brown GRAVEL WITH SAND. Slight odor.	15	SW	30	65	5	W
15							Well graded dark brown SAND. Some subrounded gravel.						
20		50/3"	70				Poorly graded red SAND with occasional silty lenses.	20	SP	--	95	5	S
24		60	60					25	SP	--	--	100	S
30	Cave-in	50/6"	80				Bottom of boring at 30 feet	30	SP SM	--	80	20	S

LOG A EWINN02 LOG A EWINN02.GPJ LOG A EWINN02.GDT 8/6/03

<b>LOGO</b>	<b>ACME CONSULTING</b> 1234 Anystreet Somewhere, Someplace Phone: 534 123 4567 Fax: 534 321 4567
	Project Location <b>Somewhere, USA</b>

<b>Lithologic Log and Well Construction Details of MW-1</b> For <b>ACME Developers, Inc.</b>		
Project No. <b>1234-ABCD</b>	Fig. <b>5</b>	