

Project: gINT Example

Boring: MW-1

Pg. 1 of 1

Drilling Co: AAAAA Drilling

Drilling Method: 8" Hollow stem flight augers Date Started: 12/16/02

Location: 30 feet north west of corner of

Sampler / Drop: 2" OD Split Spoon/30" Date Completed: 12/17/02

State & Main streets.

Logged by: I. Core Reviewed by: A. Bore

Surface Elev.: 123.4 MSL

Water Depths: ∇ ATD 24 ∇ At Completion 20

DEPTH - FT.	FIELD BOX WITH LOCKING CAP	N VALUE	% RECOVERY	PID	SAMPLES	GRAPHIC LOG	DESCRIPTION	DEPTH - FT.	USCS SYMBOL	ESTIMATED % OF			MOISTURE
										GR	SA	FI	
0							Well graded brownish-red GRAVEL WITH SAND. Cobbles present. Gravel is subrounded to rounded.						
5	CEMENT GROUT	60	100	999	X		grades sandier	5	GW	65	30	5	D
10	BENTONITE PELLETS 2 INCH SCH. 40 PVC BLANK CASING 2 INCH SCH. 40 PVC 0.020" SLOT SIZE SCREENED CASING	40	90	9999	X		Well graded brownish-red GRAVELLY SAND. Occasional cobbles.	10	SW	35	60	5	M
15	FILTER PACK, CSSI 8-12	34	80		X		Poorly graded reddish brown GRAVEL WITH SAND. Slight odor. Well graded dark brown SAND. Some subrounded gravel.	15	SW	30	65	5	W
20		50/ 3"	70		X		Poorly graded red SAND with occasional silty lenses.	20	SP	--	95	5	S
25		60	60		X			25	SP	--	--	100	S
30	Cave-in	50/ 6"	80		X		Bottom of boring at 30 feet	30	SP SM	--	80	20	S

LOG A EWINN02 LOG A EWINN02.GPJ LOG A EWINN02.GDT 7/21/04

LOGO

ACME Consulting
 1234 Main Street
 Somewhere, SOMEPLACE
 Phone: (000) 555-1234
 Fax: (000) 555-4321

Lithologic Log and Well Construction Details of MW-1
 For
ACME Developers, Inc.

Project Location Somewhere, USA	Project No. 1234-ABCD	Fig. 5
-------------------------------------------	---------------------------------	------------------