

LOGO

ACME Consulting
1234 Main Street
Telephone: (000) 555-1234
Fax: (000) 555-4321

BORING NO. **B-1**
PROJECT **gINT Example**
LOCATION **Somewhere, USA**
PROJECT NO. **ABC-123456789**
LOGGED BY **A. Bore**

SHEET **1** OF **2**

COORDINATES **N 123,456.7 E 765,432.1**
SURFACE ELEVATION **1234.5** DATUM **MSL**

SAMPLE INFORMATION						STRATA	DESCRIPTION	WELL CONSTRUCTION DETAIL	ELEVATION FEET	
DEPTH FEET	LAB SAMPLE	SAMPLE TYPE	BLOW COUNTS	Recovery %	PID (ppm)					
0-5		SS 1	2-1 1-2	80		POORLY GRADED SAND, fine, brown, dry, very loose, trace organics	Bentonite Pellets	1230		
5-10		SS 2	10-25 30	95	4321				SILTY GRAVEL, fine to coarse gravel, non-plastic silt, reddish-brown, moist, dense	Water level 1 hour after drilling
10-15	S-1	SH 3	Pushed	95					SILTY SAND, white, wet to saturated, medium dense	Water level ATD
15-20		SS 4	13-14 15-16			FAT CLAY, high plasticity, tan, saturated, very stiff, with strong organic odor	Schedule 40 Blank PVC pipe backfilled with Slough	1220		
20-25	S-2	SS 5	15-20 26-29	50					POORLY GRADED SAND, fine, pinkish-white, saturated, dense	Bentonite Pellets
25-30						ELASTIC SILT, high plasticity, tan and gray mottled, very stiff	Schedule 40 PVC pipe with 0.020" slots backfilled with Monterey Sand	1210		
30-35		SH 6	Pushed	80					Bentonite Pellets	1205
35-40								1200		

LOG A EWN03 LOG A EWN03.GPJ LOG A EWN03.GDT 7/20/04

DRILLING CONTRACTOR **AAAAA Drilling**
 DRILLING METHOD **Hollow Stem Auger**
 DRILLING EQUIPMENT **ACME Z-99**
 DRILLING STARTED **12/3/97** ENDED **12/4/97**

REMARKS **The hole is 50 feet northwest of the intersection of State and Main streets. The weather is warm and dry. Site is hilly and covered with dense brush.**

 See key sheet for symbols and abbreviations used above.

LOGO

ACME Consulting
1234 Main Street

Telephone: (000) 555-1234
Fax: (000) 555-4321

BORING NO. **B-1**
PROJECT **gINT Example**
LOCATION **Somewhere, USA**
PROJECT NO. **ABC-123456789**
LOGGED BY **A. Bore**

SHEET **2** OF **2**

COORDINATES **N 123,456.7 E 765,432.1**

SURFACE ELEVATION **1234.5** DATUM **MSL**

SAMPLE INFORMATION						STRATA	DESCRIPTION	WELL CONSTRUCTION DETAIL	ELEVATION FEET
DEPTH FEET	LAB SAMPLE	SAMPLE TYPE	BLOW COUNTS	Recovery %	PID (ppm)				
40	S-3	SS 7	19-36 38-49	60			ELASTIC SILT, high plasticity, tan and gray mottled, very stiff (<i>continued</i>)	Cement Grout	1195
45							POORLY GRADED SAND, medium, reddish-brown, very dense, with clay seams	Cave-in	1190
50		SS 8	20-60	20			POORLY GRADED GRAVEL, very dense, coarse, gray		1185
Boring terminated at 51.0 feet									