



ACME Consultants
 1234 Main Street
 Sometown, SOMEPLACE
 Telephone: (000)555-1234
 Fax: (000)555-4321

LOG OF: **MW-1**
 (1 of 1)

Project Number: **1234-ABCD**

Client: ABC Developers, Inc.			Drilling Company: AAAAA Drilling		
Project: gINT Example			Driller: I. Core		
Location: Somewhere, USA			Boring Method: 3.25 inch I.D. HSA		
North: 1,235		East: 5,432		Logged By: A. Bore	
Total Depth: 18.8	Elev GS: 123.4	Datum: MSL		Completion Date: February 12, 2003	

Sample Type/No.	Blow Counts	Rec (%)	SOIL DESCRIPTION	Depth (feet)	PID (ppm)	WELL LOG	REMARKS
SS 1	5 4 3	100	GRAVEL PAD SANDY LEAN CLAY (CL) firm, low to moderate plasticity, fine sand, tan to brown, dry	0 - 2	ND		Cement-Bentonite Grout 2 inch PVC Riser Pipe
				2 - 4			Bentonite Pellets
SS 2	5 4 4	83	CLAYEY SAND (SC) loose, fine to medium, low to moderate plasticity, gray to brown, moist	4 - 6	100		Monterey Sand Filter Pack Difficult drilling between 7 and 11 feet
				6 - 8			8.7
SS 3	8 7 8 7	92	SILTY SAND (SM) loose, fine, non-plastic, black, wet	8 - 12	1000		Hydrocarbon odor 2 inch PVC Screen with 0.02 inch machined slots
			saturated	12 - 14			Water Level 2 hours after well development
SS 4	20 25 30	94	with some fine gravel	14 - 16	100		Water Level ATD Bentonite Pellets
				16 - 17			17
SS 5	30 50/4"	52		17 - 18	ND		Cave-in
			Boring terminated at 18.8 ft	18 - 18.8			18.8
				18.8 - 20			

LOG A EWNN07 LOG A EWNN07.GPJ LOG A EWNN07.GDT 1/11/04