

LOG OF BOREHOLE B-1

Date Drilled: 01/15/2003 Logged by: A. Bore Project Manager: ABC
 Equipment: 8" Hollow Stem Auger Driving Weight and Drop: 140 lb / 30 in
 Surface Elevation (ft): 123.4 Depth to Water(ft): ▼ 5.0

DEPTH (ft)	GRAPHIC LOG	SUMMARY OF SUBSURFACE CONDITIONS	SAMPLES		BLOWS/FOOT (Equiv. SPT)	MOISTURE (%)	DRY UNIT WT. (pcf)	LABORATORY TESTS
			DRIVE	BULK				
5	▼	SILTY SAND (SM): light brown. - color change to dark brown, medium dense, moist to wet, fine to medium grained, trace clay	X	[Cross-hatched]	18	11.1	123.9	SV
10		- loose, moist, micaceous, fine to medium grained, trace fine gravel, some clay	X		8	20.9	111.3	
15	[Diagonal lines]	CLAYEY SAND (SC): dark brown, loose, moist, fine to medium grained, slightly porous	X	[Cross-hatched]	25	24.8	105.4	LL PL
20		- grades denser and gravelly	X		30			
25	[Stippled]	POORLY GRADED SANDY GRAVEL (GP): light brown, dense to very dense	X		50/6"			
		Bottom of hole at 25.5 feet						
30								
35								

LOG-A-GNNIN01.GPJ LOG-A-GNNIN01.GDT 4/16/03

Logo	ACME CONSULTING 1234 Anystreet Somewhere, Someplace Phone: 534 123 4567 Fax: 534 321 4567	gINT Tutorial Someburg, California 999-1	Plate A-3
-------------	--	--	-------------------------