



ACME Consulting
 1234 Main Street
 Somewhere, SOMEPLACE
 (000) 555-1234 Fax: (000) 555-4321

BOREHOLE B-1

Project Name: gINT Example Project No: 1234-ABCD
 Location: Somewhere, USA Client: ACME Designers
 Drilling Method: Hollow Stem Auger Date Drilled: 11/13/2002
 Elevation: 123.4 MSL Water Level: 15 ATD, 12.5 two hours after drilling
 Remarks: Hole is 70 feet northwest of intersection of State and Main streets

DEPTH FT.	DESCRIPTION	SAMPLE TYPE	BLOWS/FT.	MOISTURE %	DRY DENSITY PCF	UNCONFINED STRENGTH PSF	REMARKS
122.9	6" asphalt pavement						
0.5	LEAN CLAY (CL) firm to stiff, low to moderate plasticity, trace fine sand, gray and brown mottled, dry						
	grades sandier						
115.4	8.0 SANDY LEAN CLAY (CL) stiff to very stiff, moderate to high plasticity, fine sand, grayish brown, wet to saturated	SS	15	10			PL = 15, LL = 25
		SH		15	90	2200	
106.4	17.0 CLAYEY GRAVEL (GC) very dense, fine to coarse gravel, moderate plasticity, gray, saturated	SS	32				
102.1	21.3 Bottom of hole at 21.3 feet	SS	50/3"				

LOG A GNNN03 LOG A GNNN03.GPJ LOG A GNNN03.GDT 7/22/04