

LOG OF BORING

ACME Consulting
 1234 Main Street
 Somewhere, SOMEPLACE
 (000) 555-1234 / Fax: (000) 555-4321



PROJECT: 99-999 FOUNDATION INVESTIGATION gINT Example 123 Main Street Somewhere, USA	BORING: B-1	
	LOCATION: See Site Plan	
	DATE: 9/9/00	SCALE: 1" = 4'

Elev.	Depth	Symbol	Description of Materials	BPF	WL	Remarks
1234.5	0.0					
1233.5	1.0	SC	CLAYEY SAND, medium to coarse-grained, with fine gravel, brown, dry to moist (Fill)			
1232.5	2.0	SM	SILTY SAND, fine to medium-grained, black, moist			
		SP SM	POORLY GRADED SAND to SILTY SAND, fine-grained, dark brown, moist, medium dense (Alluvium)	20		
				12		
1227.5	7.0					
		CL	SANDY CLAY, low to moderate plasticity, fine to medium-grained, with fine gravel, brown to light brown, wet, loose	8		MC = 18% %<#200 = 65
					▽	9' first encountered
1222.5	12.0				▼	11' after removal of augers
		SW	WELL GRADED SAND, fine to coarse-grained, with some fine gravel, light brown, saturated, medium dense	26		
					⊠	14' caved level
			grading finer	19		
1215.5	19.0					
1214.0	20.5	SP	POORLY GRADED SAND, fine to medium-grained, light brown, very dense	50/6"		
			END OF BORING			
			Boring immediately backfilled			

LAGNIN06 LAGNIN06.GPJ LAGNIN06.GDT 7/22/04